

Kolor Kote®

Metal & Acrylic Roof Coating Paint

Manufacturer:

Conklin Company Inc.
551 Valley Park Drive
Shakopee, Minnesota 55379
(800) 888 – 8838 Fax (952) 496 – 4285

Product Description:

Basic use: Kolor Kote® is a finish coat which is available in four different tints and 940 colors. It is a finish coat for metal surfaces after application of Metal Ready® Universal rust inhibiting primer.

Limitations: Must not be applied at temperatures below 40°F or during inclement weather. Surface temperature must be at least 5°F above dew point and relative humidity less than 80 percent to ensure dry surfaces. Must be mixed thoroughly before use.

Sizes: Available in 5-gallon containers, 55-gallon drums and 220-gallon mini-bulk.

Coverage Rate: Coverage rates will vary depending on roof condition. Kolor Kote should yield an application rate of 200 sq. ft. per gallon in one coat. Additional coats may be required depending on surface texture.

Companion Products:

- Rust-Off® rust and oxide film remover
- Wall-Up® acrylic latex coating for masonry
- Rapid Roof® III acrylic latex roof coating
- Rapid Roof® HV acrylic latex roof coating
- Benchmark® acrylic latex roof coating
- PUMA® XL polyurethane modified acrylic roof coating
- Encase Metal Primer

Product Properties:

Resin Type	Acrylic
Color	940 colors
Coverage	200 sq. ft./gallon
Density	12.0 lbs./Gallon
Thickness	3 Dry Mills
Temperature:	Do not apply at temperatures less than 40° F. or during inclement weather
Dry Time*	1 to 3 hours
Fire Resistance**	Not combustible
Number of Coats	One Coat
VOC Content	75 g/L (0.63 lb./gal.)
Solids % by weight	Varies by base tint
Solids % by volume	Varies by base tint
Solvent	Water

*Dry time for Kolor Kote will vary depending on temperature, humidity, thickness at which the product is applied and wind. Lower wind speed, higher humidity or higher wet film thickness will increase the dry time in excess of the reported average.

**Refer to Underwriters Laboratories Roofing Materials and Systems directory for specific fire resistant assemblies or contact Conklin Company Building Products Division.

Application

Kolor Kote®

Metal & Acrylic Roof Coating Paint

Mixing/thinning: Mix thoroughly before use.

Surface Preparation: The cured Metal Ready Universal, Rapid Roof III, Rapid Roof HV, Benchmark, PUMA, PUMA XL, and Wall-Up surface must be free of all moisture, dirt, dust, and debris prior to application of Kolor Kote finish coat.

Application: Apply Kolor Kote finish coat with roller, brush, or sprayer at the recommended application rate. The minimum dry mill thickness of the completed Kolor Kote application is 3.0 dry mils.

Disposal:

Dispose of product in accordance with local state and federal regulations governing hazardous waste.

Safety:

Warning: HARMFUL OR FATAL IF SWALLOWED. CONTACT A PHYSICIAN IMMEDIATELY. Keep out of the reach of children. If spraying use a NIOSH-approved dust/mist mask.

First Aid: Eyes – immediately flush with plenty of water for at least 15 minutes. If a contact lens is present, **DO NOT** delay irrigation or attempt to remove the lens until flushing is complete. Skin – wash with soap and water, followed by a thorough rinse. Ingestion, if swallowed, **DO NOT INDUCE VOMITING**, dilute with three to four glasses of water. Immediately call a Poison Control Center or physician for further instructions. Inhalation – immediately move to fresh air.

For US Health Hazard Information, call:

1-888-786-0974

Proposition 65 Statement: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

VOC Concentration: as applied (less water and exempt solvents): **75 g/L** (0.63 lbs./gal.)

Storage:

Keep containers tightly closed when not in use. Store in a cool place, above 40° F. Keep from freezing.

Clean-up:

While the coating is still wet, clean yourself, tools and the area with water. If the coating is not fully dry, it can easily be removed with a solution of MOX® Multipurpose Cleaner and water.

CONKLIN COMPANY INC. SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES FROM ANY CAUSE WHATSOEVER. THIS GUARANTEE IS IN LIEU OF THE IMPLIED WARRANTY OF MERCHANTABILITY AND ALL OTHER WARRANTIES EXPRESSED OR IMPLIED. THIS GUARANTEE APPLIES ONLY TO THE CONKLIN INDEPENDENT BUSINESS OWNER WHO PURCHASES THE PRODUCT AND CANNOT BE EXTENDED TO ANY OTHER PERSON.



©Conklin Company Inc. 2015